# ROTOR SAT DIVISION

Rotor Sat Division - Rotors - Rotors

DATASHEET

## HH100

F205050

Satellite antenna rotor - USALS with SAT FINDER

| | |
|---|---|
| Communication Protocol | DiSEqC1.2 |
| Antenna Maximum Diameter | 100 Cm |
| Maximum Antenna Weight | 12 Kg |
| Support Pole Diameter | 50 ÷ 83 Mm |
| Lunghezza Perno Mobile | 125 Mm |
| Diametro Perno Mobile | 54 Mm |
| Rotation Angle | ± 62° |
| Rotation Speed | 1.8°/s (18 V); 1.2°/s (13 V) |
| Work Voltage | 13 / 18 Vdc |
| Stand-by Consumption | 30 MA |
| Work Absorption | 190 MA |
| Max Consumption | 350 MA |
| Operating Temperature | -40°C ÷ +80°C |
| Max Relative Humidity | 100% |
| Settable Positions (DiSEqC1.2) | 49 Satellites |
| Preset Positions (DiSEqC1.2) | 28 Satellites |
| Settable Positions (USALS) | Without Limits |
| Connectors | F-type |
| Link | Coaxial Cable |
| Mechanical Limits | ± 70° |
| Settable Electronic Limits | 5° ÷ 65° |
| Fine Rotation | 0.1° Impulses |
| Inclinazione Del Rotore Sul Palo | 15° ÷ 70° |